



NATURAL CLEAN

CLEANING AGENT

ITEM NUMBER NATURAL CLEAN

DESCRIPTION

Natural Clean is a biodegradable solvent occurring in nature as the main component of orange peel oil. Natural Clean has a positive environmental profile and pleasant orange aroma. Natural Clean can be used in its pure form, blended with other solvents or easily emulsified to make water soluble cleaning products. Natural Clean is 100% bio-based and is GRAS (Generally recognized as safe) rates.

INDUSTRY USES

Natural Clean is a safer alternative to toxic, hazardous and dangerous petroleum-derived chemicals. It can be used to formulate parts cleaner, engine degreaser, and electronic cleaner, tar cleaner, asphalt release agent, graffiti remover, grease trap maintainer, heat transfer fluid, lift station and sewage treatment solvent. Also used to remove stains, oils, grease and other contaminants from concrete surfaces.

FEATURES AND BENEFITS

- Made in America
- Pleasant orange scent, non-toxic, non-flammable, non-carcinogenic
- Made from recycling orange peels
- 100% biodegradable, non-hazardous waste

PACKAGING

5 gal pail (18.9L)

TECHNICAL DATA

| | |
|------------------------|---|
| Shelf Life: | 2 years in original packaging and unopened container. |
| Storage Conditions: | 40° F – 95° F (5° C – 35° C) |
| Condition Material to: | 65°F-85°F (18°C-29°C) |
| Color | Colorless to pale yellow liquid |
| Odor | Strong orange aroma |
| Solubility | Immiscible with water |
| Specific Gravity 25° C | 0.838 – 0.843 |
| Refractive Index 20° C | 1.471 – 1.474 |
| Optical Rotation 25° C | +96.0° - +104.0° |
| Flash Point CCCP | >110°F |

APPLICATION

| | Dilution Ratio (Recommended % of Concentrate in Water) |
|--|---|
| Adhesive Removal and Clean Up | 10 to 100% |
| Electronic Contact and Switch Cleaner | 100% |
| Electronic Motor Winding | 100% |
| Epoxy and Mold Cleaning | 25 to 100% |
| Industrial Air Freshener | 90% |
| Paints – Brush and Equipment Cleanup | 10 to 100% |
| Paints – Painting Preparation | 10 to 100% |
| Paving Equipment Cleaning | 100% |
| Repairs and Maintenance – General Hand Cleaning | 20 to 30% |
| Repairs and Maintenance – Parts and Equipment Cleaning | 25 to 100% |
| Resins and Plastics Manufacturing | 100% |
| Warehouses – General Cleaning | 10 to 20% |



NATURAL CLEAN

CAUTION

Safety Considerations

- Keep away from heat, sparks, flame.
- Open container slowly to release pressure caused by temperature variations.
- Use of safety goggles and chemical resistant gloves are recommended
- Use in well ventilated areas
- Avoid breathing vapors
- Avoid skin contact

First Aid

- **EYE CONTACT:** Remove contact lenses. Flush immediately with water for at least 15 minutes. If irritation persists, contact physician immediately.
- **RESPIRATORY CONTACT:** If symptoms of overexposure are experienced, Remove person to fresh air. If irritation persists, contact physician immediately.
- **SKIN CONTACT:** Remove any contaminated clothing. Wash skin thoroughly with soap and water. If irritation persists, contact physician immediately.
- **INGESTION:** Seek medical attention immediately. DO NOT induce vomiting. Rinse mouth with water. DO NOT administer anything by mouth to an unconscious person. DO NOT leave victim unattended.

WARRANTY

KEEP CONTAINER TIGHTLY CLOSED – KEEP OUT OF REACH OF CHILDREN – NOT FOR INTERNAL CONSUMPTION – FOR INDUSTRIAL USE ONLY

All information provided by Cornerstone Construction Material LLC (CCM) concerning CCM products, including but not limited to, any recommendations and advice relating to the application and use of CCM products, is given in good faith based on CCM's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with CCM's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of CCM's control are such that CCM assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the CCM product(s) must test the product(s) for suitability for the intended application and purpose before proceeding the full application of the product(s). CCM reserves the right to change the properties of its products without notice. All sales of CCM product(s) are subject to its current terms and conditions of sale which are available by calling 816-380-1082.

Prior to each use of any CCM product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Material Safety Data Sheet which are available by emailing support@ccmaterial.com or calling 816-380-1082. Nothing contained in any CCM materials relieves the user of the obligation to read and follow the warnings and instruction for each CCM product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use.

LIMITED WARRANTY: CCM warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet if used as directed within the shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. CCM SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. CCM SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.