



CE350 EPOXY JOINT FILLER

SEMI-REGID EPOXY CONTROL JOINT FILLER

ITEM NUMBER CE350

DESCRIPTION

CE350 Epoxy Joint Filler is a two-component, 100% solids, moisture-tolerant, semi-rigid, flexible, self-leveling epoxy joint filler and sealer.

WHERE TO USE

Used to fill and seal horizontal saw-cut control joints and random cracks.

ADVANTAGES

- May be used on damp or dry surfaces
- Pourable consistency, concrete grey
- Made in America
- Convenient 1:1 mix ratio by volume

COVERAGE

1 Gal yields 231 cu in or 3,780 cu cm.

PACKAGING

- 2 gal / 7.6 L units
- 10 gal / 38 L units

TECHNICAL DATA

Shelf Life:	2 years in original unopened container.	
Storage Conditions:	40°F – 95°F (5°C – 35°C).	
Condition material to:	65°F – 85°F (18°C – 29°C) before using.	
Mix Ratio	1:1 by volume	
Consistency	Self-leveling	
Gel Time (60 g mass)	30 minutes	
Tack Free Time (73°F or 23°C)	3 to 5 hours	
Hardness (ASTM D2240)	Shore A	80-90
	Shore D	55-65

APPLICATION

SURFACE PREPARATION: Surface must be clean and sound. Surface must be free of standing water. Remove curing compounds-latency, grease, rubber and any foreign matter or unsound surface.

MIXING: Pre-mix each component thoroughly. Mix only the amount of material that can be used within its pot life. Proportion each component carefully into a clean pail. Mix thoroughly for 3 minutes with a Jiffy mixer on low speed (400-600rpm). Scrape the sides and bottom of the container.

Placement: Use a caulking gun or pour directly to the joints. Overfill the joints. Once tack-free, cut the CE350 with a razor life. A heat gun can facilitate cutting the CE350 Epoxy joint.

LIMITATIONS

Minimum substrate temperature is 50°F (10°C). Do not thin. Solvents will prevent proper cure. Use oven-dried aggregate. Material is a vapor barrier after cure.

CLEAN UP

Collect with absorbent material. Flush area with water. Dispose of in accordance with local, state and federal disposal regulations. Uncured material can be removed with CE Clean or approved solvent. Cured material can only be removed mechanically.



CE350 EPOXY JOINT FILLER

LIMITED WARRANTY

All information provided by Cornerstone Construction Material LLC (CCM) concerning CCM products, including but not limited to, any recommendations and advice relating to the application and use of CCM products, is given in good faith based on CCM's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with CCM's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of CCM's control are such that CCM assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the CCM product(s) must test the product(s) for suitability for the intended application and purpose before proceeding the full application of the product(s). CCM reserves the right to change the properties of its products without notice. All sales of CCM product(s) are subject to its current terms and conditions of sale.

Prior to each use of any CCM product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Safety Data Sheet which are available at www.ccmaterial.com. Nothing contained in any CCM materials relieves the user of the obligation to read and follow the warnings and instruction for each CCM product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use.

CCM warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet when used in accordance with the written instructions. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. CCM SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. CCM SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.