



**PERFORMANCE  
CONSTRUCTION  
PRODUCTS**

PERFORMANCE, CONSISTENCY, SERVICE

---

# TABLE OF CONTENTS

---

| <b>Product Group</b>                             | <b>Page</b> |
|--|-------------|
| Rapid Strength Cement                            | 2           |
| Cement Repair Mortars & Concretes                | 2 & 3       |
| Hydraulic Cement                                 | 3           |
| Anchoring Cement                                 | 3           |
| Non-Shrink Grouts                                | 4           |
| Epoxy Binder                                     | 4           |
| Epoxy Healer / Sealer                            | 5           |
| Polymer Deck Sealer                              | 5           |
| Pavement Sealant                                 | 5           |
| Epoxy Joint Filler                               | 5           |
| Epoxy Floor Coatings – Protective and Decorative | 6           |
| Hybrid Polymer Concrete                          | 6           |
| Epoxy Repair Mortars                             | 6           |
| Epoxy Repair Mortars – Polymer Nosing System     | 6           |
| Epoxy Repair Mortars – All Weather Repair System | 7           |
| Epoxy Grout                                      | 7           |
| Epoxy Chock                                      | 7           |
| Epoxy Construction Adhesives                     | 8           |
| Cleaners   | 9           |
| Cure and Seal                                    | 9           |
| Tools & Equipment                                | 9           |
| Terms & Conditions of Sale                       | 10          |

## RAPID STRENGTH CEMENT

| Product Name              | Packaging   | Description  | Freight Class |
|---------------------------|---|--|---------------|
| <b>FasTrac 300 Cement</b> | <ul style="list-style-type: none"> <li>50 lb. bag (56/pallet)</li> <li>2000 lb. super sack</li> <li>Bulk</li> </ul> | One-component, rapid hardening, low shrinkage, extendable cement that is used when high early strength gain is required. FasTrac 300 Cement is mixed with aggregate and water on site for large scale horizontal concrete repairs and form and pour vertical applications  | 50            |
| <b>FasTrac 220 Cement</b> | <ul style="list-style-type: none"> <li>50 lb. bag (56/pallet)</li> <li>2000 lb. super sack</li> <li>Bulk</li> </ul> | One-component, shrinkage compensated, proprietary blend of cementitious materials and performance enhancing chemical additives. This rapid setting cement blend is mixed with aggregate and water on site, used for large-scale horizontal concrete repairs, and form and pour vertical applications that require high early-strength gain. For low permeability applications. | 50            |
| <b>FasTrac 303 Cement</b> | <ul style="list-style-type: none"> <li>50 lb. bag (56/pallet)</li> <li>2000 lb. super sack</li> <li>Bulk</li> </ul> | One-component, rapid hardening, low shrinkage, extendable cement that is used when high early strength gain, low permeability, and latex modification is required. FasTrac 303 Cement is mixed with aggregate, latex, and water on site for large scale horizontal concrete repairs and form and pour vertical applications.   | 50            |
| <b>FasTrac 400 Cement</b> | <ul style="list-style-type: none"> <li>50 lb. bag (56/pallet)</li> <li>2000 lb. super sack</li> <li>Bulk</li> </ul> | One-component, ultra-rapid hardening, low shrinkage, extendable cement that is used when high early strength gain is required. FasTrac 400 Cement is mixed with aggregate and water on site for large scale horizontal concrete repairs and form and pour vertical applications  | 50            |

## CEMENT REPAIR MORTARS & CONCRETES

| Product Name   | Packaging  | Description   | Freight Class |
|--|--|---|---------------|
| <b>FasTrac 246 Concrete</b><br>Rapid Setting Concrete              | <ul style="list-style-type: none"> <li>60 lb. bag (56/pallet)</li> <li>600 lb. mini super sack</li> <li>3000 lb. super sack</li> </ul> | One-component, shrinkage compensated, proprietary blend of cements, aggregates, and performance enhancing chemical additives. This rapid setting concrete is mixed with water on site, used for large-scale horizontal concrete repairs, and form and pour vertical applications that require rapid strength gain and low permeability. | 50            |
| <b>FasTrac 246 Mortar</b><br>Rapid Setting Repair Mortar           | <ul style="list-style-type: none"> <li>60 lb. bag (56/pallet)</li> <li>600 lb. mini super sack</li> <li>3000 lb. super sack</li> </ul> | Single component, very rapid setting, pre-extended concrete for horizontal highway and industrial concrete repair. Form and pour vertical applications requiring rapid strength gain. Can be extended with a clean 3/8" aggregate.  | 50            |
| <b>FasTrac Structural Shotcrete</b><br>Multi-Purpose Repair Mortar | <ul style="list-style-type: none"> <li>50 lb. bag (56/pallet)</li> <li>600 lb. mini super sack</li> <li>3000 lb. super sack</li> </ul> | FasTrac Shotcrete is a high performance, one component pre-blended, silica fume enhanced, fiber reinforced, cement-based product. This product is designed to be used for wet or dry spraying process.  | 50            |

|  |   |  |    |
|--|---|--|----|
| <b>FasTrac Infinity</b>                                  | <ul style="list-style-type: none"> <li>60 lb. bag (56/pallet)</li> </ul>  | General purpose, one-component, rapid setting, polymer modified, non-shrinking grout that is used when rapid strength gain is required. FastPatch Infinity is mixed with water on site for virtually any type of fast concrete repairs.  | 50 |
| <b>FasTrac Resurfacer</b>                                | <ul style="list-style-type: none"> <li>60 lb. bag (56/pallet)</li> </ul>  | Two-component, rapid setting, low shrinkage mortar that is used to overlay existing pavements and floors. FasTrac ReSurfacer is mixed with FasTrac polymer on site and is placed with suitable placement equipment and finished to the desired texture. Provides tenacious bond. | 50 |
| <b>FasTrac Polymer</b>                                   | <ul style="list-style-type: none"> <li>5 gal pail (36/pallet)</li> <li>55 gal drum</li> <li>250 gal tote</li> </ul> | A unique formulation of various polymers and modifiers designed for use as an additive for cement mixes. FasTrac Polymer can be used as a bonding agent or polymer modifier for thin screeds or to modify concrete for superior bonding and extremely low permeability.          |    |
| <b>FasTrac VO</b><br>Vertical Overhead<br>Repair Mortar  | <ul style="list-style-type: none"> <li>50 lb. bag (56/pallet)</li> </ul>  | Vertical Overhead Mortar is a single component, polymer-modified, cement-based mortar with corrosion inhibitor for structural repairs of deteriorated concrete.  | 50 |
| <b>FasTrac Concrete Finisher</b><br>Thin Wall Resurfacer | <ul style="list-style-type: none"> <li>50 lb. bag (56/pallet)</li> </ul>  | One component cement based concrete coating material. Provides excellent adhesion, fills and levels concrete surfaces and is highly durable. Trowel or spray applied.  | 50 |
| <b>FasTrac Cement Wash</b>                               | <ul style="list-style-type: none"> <li>50 lb. bag (56/pallet)</li> </ul>  | FasTrac Cement Wash is a single-component, polymer-modified, cement-based material used for achieving an ultra-smooth finish on precast, cast-in-place, tilt-up or other unfinished concrete surfaces. This product offers superior adhesion and durability.                     | 50 |

## HYDRAULIC CEMENT

| Product Name  | Packaging   | Description   | Freight Class |
|---|---|---|---------------|
| <b>Hydraulic Cement</b><br>Repair Active Water<br>Leaks | <ul style="list-style-type: none"> <li>50 lb. pail</li> <li>50 lb. bag</li> </ul> | A single component, ready to use, expanding, hydraulic cement-based water-stop mortar. Designed to stop active water and seeping water through cracks in concrete and masonry under hydrostatic pressure. | 50            |

## ANCHORING CEMENT

| Product Name  | Packaging   | Description  | Freight Class |
|---|---|--|---------------|
| <b>Anchoring Cement</b><br>Pourable Anchoring<br>Cement | <ul style="list-style-type: none"> <li>50 lb. pail</li> <li>50 lb. bag</li> </ul> | A single component, ready to use, rapid setting and hardening, pourable, fast-setting, anchoring cement. Non-gypsum formula. Controlled expansion – non-shrink. Obtains 5,000 psi in one hour. | 50            |

## NON-SHRINK GROUTS

| Product Name  | Packaging  | Description   | Freight Class |
|---|--|---|---------------|
| <b>FasTrac HP Grout</b><br>Precision Cement Grout                       | <ul style="list-style-type: none"> <li>• 50 lb. bag (56/pallet)</li> <li>• 3000 lb. bag</li> </ul> | A hydraulic-cement-based, precision, non-shrink, load-bearing grout having an extended working time and excellent flow characteristics. Non-corrosive, non-metallic, mineral-based developed to have a high initial and ultimate flexural and compressive strength. Offers exceptional workability by pouring or pump. ASTM C 1107 and CRD C 621. | 50            |
| <b>FasTrac NS Grout</b><br>Multi-Purpose<br>Construction Grade<br>Grout | <ul style="list-style-type: none"> <li>• 50 lb. bag (56/pallet)</li> <li>• 3000 lb. bag</li> </ul> | A specially formulated for construction grade non-shrink for industrial applications. This non-shrink, non-metallic grout does not contain chloride and can be used in range of consistencies from plastic to fluid. MP Grout meets ASTM C1107 Grade C  | 50            |
| <b>Aqua Grout</b><br>Pumpable Underwater<br>Grout                       | <ul style="list-style-type: none"> <li>• 50 lb. bag (56/pallet)</li> <li>• 3000 lb bag</li> </ul>  | A high precision, non-shrink, natural aggregate, cementitious grout designed to be mixed and placed for underwater or tidal zone grouting applications.   | 50            |

## EPOXY BINDER Bridge and Pavement Rehabilitation

| Product Name                                      | Packaging   | Description   | Freight Class |
|---|---|---|---------------|
| <b>CE330</b><br><b>Epoxy Binder</b><br>1: 1 ratio | <ul style="list-style-type: none"> <li>• 1.0 gal</li> <li>• 2.0 gal</li> <li>• 10.0 gal</li> <li>• 110.0 gal</li> <li>• 500.0 gal</li> </ul> <b>Cartridges</b> <ul style="list-style-type: none"> <li>• 600 ml / 20.28 ounces</li> <li>• 12 per case / Includes static mixing nozzle</li> </ul> | A two-component, 100% solids, moisture-tolerant, low to <b>medium viscosity</b> , high strength, low modulus, multi-purpose liquid epoxy binder. ASTM C881 and AASHTO M235, Type III, Classes B & C specifications.   | 55            |
| <b>CE330</b><br><b>Demarc Pro</b>                 | <ul style="list-style-type: none"> <li>• 1.0 gal</li> <li>• 2.0 gal</li> <li>• 10.0 gal</li> <li>• 110.0 gal</li> <li>• 500.0 gal</li> </ul> <b>Cartridges</b> <ul style="list-style-type: none"> <li>• 600 ml / 20.28 ounces</li> <li>• 12 per case / Includes static mixing nozzle</li> </ul> | A two-component, 100% solids, moisture-tolerant, low to medium viscosity, high strength, low modulus, multi-purpose liquid epoxy binder formulated for use with colored crushed glass and other aggregates. Apply to approved substrates with approved aggregates to reduce pedestrian, cyclists and vehicular incidents. Add increased awareness, friction, aesthetics, safety and long-term durability. | 55            |

## EPOXY HEALER / SEALER Concrete Deck Crack Sealer

| Product Name                                 | Packaging   | Description   | Freight Class |
|--|---|---|---------------|
| <b>CE335<br/>Healer Sealer</b><br>1: 1 ratio | <ul style="list-style-type: none"> <li>• 2.0 gal</li> <li>• 10.0 gal</li> <li>• 110.0 gal</li> <li>• 500.0 gal</li> </ul> | A two-component, 100% solids, moisture insensitive, <b>low viscosity</b> crack healer and high elongation penetrating epoxy sealer. ASTM C881 and AASHTO M235, Type III, Grade 1, Classes B & C specifications. | 55 H          |

## POLYMER DECK SEALER Concrete Deck Flood Coat

| Product Name                                    | Packaging   | Description  | Freight Class |
|---|---|--|---------------|
| <b>CE335 FC<br/>Bridge Sealer</b><br>1: 1 ratio | <ul style="list-style-type: none"> <li>• 2.0 gal</li> <li>• 10.0 gal</li> <li>• 110.0 gal</li> <li>• 500.0 gal</li> </ul> | A two-component, 75% solids, moisture insensitive, <b>ultra - low viscosity</b> , epoxy sealer. High elongation. Structurally penetrates and strengthens the concrete substrate. | 55 H          |

## PAVEMENT SEALANT

| Product Name                     | Packaging   | Description  | Freight Class |
|----------------------------------|---|--|---------------|
| <b>CE604</b><br>Pavement Sealant | <ul style="list-style-type: none"> <li>• 1.0 gal</li> <li>• 2.0 gal</li> <li>• 10.0 gal</li> </ul> 12 per case / includes mixing nozzle & flow restrictor | A two-component, 100% solids, moisture-insensitive, low viscosity, low modulus, flexible concrete and asphalt crack sealant. | 55 H          |

## EPOXY JOINT FILLER

| Product Name                                | Packaging  | Description  | Freight Class |
|---|--|--|---------------|
| <b>CE350<br/>Joint Filler</b><br>1: 1 ratio | <ul style="list-style-type: none"> <li>• 2.0 gal</li> <li>• 10.0 gal</li> <li>• 110.0 gal</li> </ul> <b>Cartridges</b> <ul style="list-style-type: none"> <li>• 600 ml / 20.28 ounces</li> </ul> 12 per case / Includes static mixing nozzle | A two-component, 100% solids, moisture-tolerant, semi-rigid, flexible, self-leveling epoxy joint filler. Designed to reduce saw cut spall back and damage to joints. | 55            |

## EPOXY FLOOR COATINGS Protective and Decorative

| Product Name                                       | Packaging  | Description  | Freight Class |
|--|--|--|---------------|
| <b>CE340 MVT</b><br>Moisture Mitigating Epoxy      | <ul style="list-style-type: none"> <li>• 2.0 gal</li> <li>• 10.0 gal</li> </ul>  | A two-component, 100% solids, low viscosity, low modulus, moisture mitigating epoxy designed for use in flooring applications  | 55 H          |
| <b>CE440</b><br><b>Epoxy Coating</b><br>2: 1 ratio | <ul style="list-style-type: none"> <li>• 1.5gal</li> <li>• 3.0 gal</li> <li>• 15.0 gal</li> <li>• 165.0 gal</li> </ul> | A <b>low viscosity</b> , two-component, solvent-free, moisture tolerant, high gloss multipurpose epoxy clear coating with high chemical resistant properties. VOC compliant. | 55 H          |

## HYBRID POLYMER CONCRETE

| Product Name                                | Packaging  | Description  | Freight Class |
|---|--|--|---------------|
| <b>CE700 HPC</b><br>Hybrid Polymer Concrete | <ul style="list-style-type: none"> <li>• Repair: 1.25 cu ft.</li> <li>• Standard: 5.0 cu ft.</li> <li>• Precision: 2.3 cu yd.</li> <li>• DOT: 11.6 cu yd.</li> </ul> | A three-component system containing the finest hybrid polymer resins and blends of specialty selected coarse aggregates. Specifically designed to resurface and restore prepared concrete surfaces from ½" to 12" in one application lift. The system can be utilized for variable depth cross sections. Return to traffic within 3 hours. | 55            |

## EPOXY REPAIR MORTARS

| Product Name                          | Packaging  | Description   | Freight Class |
|---------------------------------------|--|---|---------------|
| <b>CE710</b><br>Epoxy Patching Mortar | <ul style="list-style-type: none"> <li>• 0.50 cu. ft.</li> <li>• 1.0 cu. ft.</li> </ul> 3 component kits | A three-component, 100% solids, multi-purpose, high strength, and non-shrink epoxy patching mortar. The system combines a high-quality epoxy resin and curing agent with an engineered blend of graded aggregates. Specifically engineered to absorb high impact and abrasion while demonstrating similar physical characteristics to the concrete substrate. | 55            |

## EPOXY REPAIR MORTARS Polymer Nosing System

| Product Name                               | Packaging  | Description   | Freight Class |
|--|--|---|---------------|
| <b>CE715<sup>PNS</sup></b><br>Epoxy Mortar | <ul style="list-style-type: none"> <li>• 0.50 cu. ft.</li> <li>• 1.0 cu. ft.</li> </ul> 3 component kits | A three-component, 100% solids, multi-purpose, high strength, non-shrink semi flexible epoxy mortar. The system combines a high-quality epoxy resin and curing agent with an engineered blend of graded aggregates. Specifically engineered for the construction or repair of expansion and construction joints on bridges and parking decks. | 55            |

## EPOXY REPAIR MORTARS All Weather Repair System

| Product Name                          | Packaging   | Description  | Freight Class |
|---------------------------------------|---|--|---------------|
| <b>CE720</b><br>Epoxy Patching Mortar | <ul style="list-style-type: none"> <li>0.50 cu. ft.</li> </ul> 3 component kits | A three component, rapid setting, 100% solids, high strength, low modulus, all-weather spall repair and patching material for concrete. The unit consists of a unique hybridized epoxy / urethane system and specially graded engineered aggregates for achieving rapid turnaround in most weather conditions. | 55 H          |

## EPOXY GROUT

| Product Name                          | Packaging  | Description  | Freight Class |
|---------------------------------------|--|--|---------------|
| <b>CE815</b><br>Epoxy Patching Mortar | <b>CE 815:</b> <ul style="list-style-type: none"> <li>0.50 cu. ft.</li> <li>2.0 cu. ft.</li> </ul> <b>CE 815ED:</b> <ul style="list-style-type: none"> <li>0.50 cu. ft.</li> <li>2.0 cu. ft.</li> </ul> 3 component kits | A three-component, 100% solids, high performance, high strength, multipurpose epoxy machine grout. High bearing area, low exothermic, negligible shrinkage and creep. Fast cure and excellent followability. | 55 H          |
| <b>CE818 HP</b>                       | <ul style="list-style-type: none"> <li>1.5 cu ft. kit</li> </ul>   | A three-component, 100% solids, high performance, high strength, multi-purpose epoxy machine grout. It is characterized by high early and ultimate strength, high bearing area and low exothermic.           | 55 H          |

## EPOXY CHOCK

| Product Name                          | Packaging  | Description   | Freight Class |
|---------------------------------------|--|---|---------------|
| <b>CE820</b><br>Precision Epoxy Chock | <ul style="list-style-type: none"> <li>.50 cu. ft.</li> </ul> 2 component kits | A two-component, 100% solids, high performance epoxy machine grout. It is characterized by high early and ultimate strength, high bearing area, low exothermic, negligible shrinkage and creep, fast cure and excellent flowability. It can also use as anchor adhesive | 55 H          |



## EPOXY CONSTRUCTION ADHESIVES

| Product Name   | Packaging   | Description  | Freight Class |
|--|---|--|---------------|
| <p><b>CE110</b><br/>Injection Resin<br/>2: 1 ratio</p>           | <ul style="list-style-type: none"> <li>• 1.5 gal</li> <li>• 3.0 gal</li> <li>• 15.0 gal</li> <li>• 165.0 gal</li> <li>• 750.0 gal</li> </ul> <p><b>Cartridges</b></p> <ul style="list-style-type: none"> <li>• 450 ml / 15.2 ounces</li> </ul> <p>12 per case / Includes static mixing nozzle</p> | <p>A two-component, 100% solids, moisture-insensitive, <b>ultra-low viscosity</b>, high strength, high modulus, multi-purpose liquid epoxy adhesive. ASTM C881 and AASHTO M235 Types I, II, IV &amp; V Grade 1, Classes B &amp; C.</p>   | 55 H          |
| <p><b>CE220</b><br/>Bonding Agent<br/>1: 1 ratio</p>             | <ul style="list-style-type: none"> <li>• 1.0 gal</li> <li>• 2.0 gal</li> <li>• 10.0 gal</li> <li>• 110.0 gal</li> </ul> <p><b>Cartridges</b></p> <ul style="list-style-type: none"> <li>• 600 ml / 20.28 ounces</li> </ul> <p>12 per case / Includes static mixing nozzle</p>                     | <p>A two-component, 100% solids, moisture-insensitive, <b>medium viscosity</b>, high strength, multi-purpose liquid epoxy adhesive. ASTM C881 and AASHTO M235, Types I, II, IV &amp; V Grade 2, Classes B &amp; C.</p>   | 55 H          |
| <p><b>CE308</b><br/>Standard Set Anchoing Gel<br/>1: 1 ratio</p> | <ul style="list-style-type: none"> <li>• 1.0 gal</li> <li>• 2.0 gal</li> <li>• 10.0 gal</li> <li>• 110.0 gal</li> </ul> <p><b>Cartridges</b></p> <ul style="list-style-type: none"> <li>• 250 ml</li> <li>• 600 ml</li> <li>• 1500 ml</li> </ul> <p>Includes static mixing nozzle</p>             | <p>A two-component, 100% solids, moisture-insensitive, high strength, high modulus, multi-purpose liquid epoxy <b>gel viscosity</b> adhesive. ASTM C881 and AASHTO M235 Types I, II, IV &amp; V Grade 3, Classes B &amp; C.</p> <ul style="list-style-type: none"> <li>• <b>CE308 Fast Set also available</b></li> </ul> | 55 H          |
| <p><b>CE550</b><br/>Segmental Bridge Adhesive</p>                | <ul style="list-style-type: none"> <li>• 3.0 gal</li> </ul>   | <p>A two-component, 100% solids, moisture insensitive, high modulus epoxy adhesive. Meets ASTM C881, Type VI. Available in low temperature, medium temperature and high temperature versions.</p>  | 55 H          |

## CLEANERS

| Product Name  | Packaging   | Description  | Freight Class |
|---|---|--|---------------|
| <b>CE Natural Clean</b><br>Citrus Based Cleanup Solvent | <ul style="list-style-type: none"> <li>5-gal pail (36/pallet)</li> <li>1-gal pail (4/case)</li> </ul> | A heavy duty, citrus based cleaner and degreaser. 100% biodegradable once reduced with water. A GREEN alternative to petroleum-based solvents.   | 55            |
| <b>CE Solv100</b><br>Aromatic 100 Cleanup Solvent       | <ul style="list-style-type: none"> <li>5-gal pail (36/pallet)</li> <li>1-gal pail (4/case)</li> </ul> | An aromatic petroleum solvent thinner and clean up material. A heavy duty, water clear, colorless, high strength chemical reducer / cleaner and everyday oil-based solvent.            | 55            |
| <b>CE Acetone</b>                                       | <ul style="list-style-type: none"> <li>5 gal pail</li> </ul>  | A highly effective, organic solvent thinner and clean up material. A high strength, extremely volatile and flammable chemical solvent. Removes epoxy residue from equipment and tools. | 55 H          |
| <b>Rhino Tough Wipes</b>                                | <ul style="list-style-type: none"> <li>70 wipes per canister</li> <li>6 canisters per case</li> </ul> | Non-toxic wipes for easy & safe epoxy clean up. Perfect for removing epoxy resins, dirt, grease, polyester resins, and many other jobsite grimes from hands and other surfaces.        |               |

## CURE AND SEAL

| Product Name   | Packaging   | Description  | Freight Class |
|--|---|--|---------------|
| <b>Cure &amp; Seal<sup>1315</sup></b><br>Solvent based | <ul style="list-style-type: none"> <li>55 gal drum</li> <li>5 gal pail (36/pallet)</li> </ul> | A VOC compliant, 25% solids, solvent based, clear acrylic curing and sealing compound. ASTM C 309, Type I, Class A & B. ASTM C 1315, Class A | 55            |

## Tools & Equipment

| Product Name                    | Packaging                |
|---------------------------------|--------------------------|
| Pneumatic Epoxy Cartridge       | 1:1 Gun / 22 ounce       |
| Manual Epoxy Cartridge          | 1:1 & 2:1 Gun / 22 ounce |
| Jiffy Mixer LM                  | Pint                     |
| Jiffy Mixer (HS-1)              | 1 – 2 gal                |
| Jiffy Mixer (ES 2)              | 5 gal                    |
| Jiffy Mixer (PS-1)              | 5 – 10 gal               |
| Jiffy Mixer (PS-2)              | 10 – 50 gal              |
| 24 “(3/8)” Squeegee with handle |                          |

# Terms & Conditions of Sale

All orders are accepted, and all sales are made in accordance with the following terms and conditions:

**PRICING:** ALL ORDERS ACCEPTED BY WESTERN MATERIAL & DESIGN (WM&D) OR CORNERSTONE CONSTRUCTION MATERIAL (CCM) ARE SUBJECT TO PRICES IN EFFECT AT TIME OF SHIPMENT. All orders are subject to approval of Purchaser's credit and final acceptance in Lee's Summit, MO.

**TERMS OF PAYMENT:** All shipments are made on NET 30 DAYS. WM&D or CCM reserves the right to require payment in full before shipment. Each shipment shall be deemed a separate and independent transaction and payment shall be made accordingly. PAST DUE ACCOUNTS ARE SUBJECT TO A 1 1/2 % PER MONTH SERVICE CHARGE OR THE MAXIMUM ALLOWABLE LEGAL NOTE, WHICHEVER IS LOWER.

**FREIGHT TERMS:** All prices are F.O.B. Factory. Risk of loss passes to Purchaser upon delivery of products to an agent of Purchaser or common carrier.

**FREIGHT CARRIERS:** Please specify freight companies for your orders. WM&D or CCM cannot be responsible for freight rates, billing errors, damage claims, freeze ability or shipping schedules of any freight company.

**SHORTAGE AND DAMAGED GOODS:** Shortages or errors in billing must be reported in writing to WM&D or CCM within five (5) days of receipt of shipment to secure adjustments. If shipments are received in a damaged condition or short in number of packages, the customer must have the carrier note this fact on delivery receipt or paid freight bill. Claim for loss and damage in transit with the transportation company is the responsibility of the customer.

**COMPLETE AGREEMENT:** The complete agreement between WM&D or CCM and Purchaser is contained herein, and no additional or different term or condition stated by Purchaser will be binding unless agreed to by WM&D or CCM in writing. The failure of WM&D or CCM to insist upon strict performance of any terms or conditions stated herein will not be considered a continuing waiver of any such term or condition or any of its rights, nor will it imply a course of performance between parties.

**TECHNICAL DATA and SAFETY DATA SHEETS:** The most current file is published on [www.wmdus.com](http://www.wmdus.com) or [www.ccmaterial.com](http://www.ccmaterial.com)

**SHELF LIFE:** Please refer to the Technical Data Sheet published on [www.wmdus.com](http://www.wmdus.com) or [www.ccmaterial.com](http://www.ccmaterial.com)

**LIMITED WARRANTY:** WM&D or CCM warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet if used as directed within the shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. WM&D SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. WM&D SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

**Western Material & Design  
&  
Cornerstone Construction Material  
1150 SE Hamblen Rd  
Lee's Summit, MO 64081**

**Customer Service & Technical Support**

**800-451-0173**

**[www.wmdus.com](http://www.wmdus.com)**

**[www.ccmaterial.com](http://www.ccmaterial.com)**